

MDU Solutions® UCrypt® ENVIRONMENT & TEMPERATURE CONSIDERATIONS

1. Purpose

This information sheet has been published to assist installers and operators of UCrypt device equipment to understand the environment temperature requirements for the installed equipment.

2. Mounting Precautions

The UCrypt device consists of a computer like device which generates heat in its normal operation and must be kept cool to ensure trouble free service and long life. It should be installed or mounted in an environment where the temperature surrounding the equipment is comfortable for a person, commonly referred to as “Room temperature”. This is typically a preferred indoor controlled temperature of between 20 and 26 °C (68 and 79 °F).

Remember that there may be a large difference between the temperature surrounding the equipment and the temperature indication on a room thermostat.

- **Avoid Elevated Operating Ambient Temperature:**
If installed in a closed environment that may exceed room ambient temperature, consideration should be given to installing the equipment in an environment that is compatible with the maximum ambient temperature specified (40°C).
- **Avoid Reduced Air Flow:**
Installation should allow at least 2” spacing around the equipment and 6” in front and rear to ensure that airflow required for proper operation is not compromised. For rack mounting, one rack unit of vertical separation is highly recommended but not strictly necessary.
- **Avoid Heat from Adjacent Equipment:**
Specifically avoid an installation where heat generated by nearby equipment exhausts at or near the UCrypt device. Externally generated heat will increase the ambient temperature and inhibit the ability of the UCrypt device to cool itself sufficiently.

3. Specified Maximum Temperature

The UCrypt device is designed to operate to specification in an ambient temperature of 0°C to +40°C (+32°F to +104°F) however, good engineering practice dictates that keeping electronic equipment cool in operation will extend its life.

Operating the UCrypt device in environments above +30°C (+86°F) will result significant shorting of equipment life and may result in alarms and warnings.



Service & Support

Contact ATX Networks

Please contact ATX Technical Support for assistance with any ATX products. Please contact ATX Customer Service to obtain a valid RMA number for any ATX products that require service and are in or out-of-warranty before returning a failed module to the factory.

Digital Video Products

(DVIS, DigiVu, UCrypt, VersActivePro)

TECHNICAL SUPPORT

Tel: (905) 428-6068 – press *3 then press 1
Toll Free: (800) 565-7488 – press *3 then press 1 (USA & Canada only)
Email: digitalvideosupport@atxnetworks.com

CUSTOMER SERVICE

ATX Networks
1-501 Clements Road West
Ajax, ON L1S 7H4 Canada

Tel: (905) 428-6068 – press *1
Toll Free: (800) 565-7488 – press *1 (USA & Canada only)
Fax: (905) 427-1964
Toll Free Fax: (866) 427-1964 (USA & Canada only)
Email: support@atxnetworks.com
Web: www.atxnetworks.com

Warranty Information

All of ATX Networks' products have a 1-year warranty that covers manufacturer's defects or failures.

Although every effort has been taken to ensure the accuracy of this document it may be necessary, without notice, to make amendments or correct omissions. Specifications subject to change without notice.

* Any use of the UCrypt product, directly or indirectly, for the decryption and unauthorized reproduction of content that constitutes or may constitute copyright infringement or otherwise infringes on the proprietary rights of any third party is expressly prohibited. No user of UCrypt shall use UCrypt for any purpose or in any manner which, directly or indirectly, violates the law, violates the proprietary rights of any other party, or aids in any unlawful act or undertaking including, without limitation, laws governing data privacy, international data transmission, and export of technology or data. Any multiple systems operator or other similar party ("MSO") will use the UCrypt product in strict compliance with all applicable laws and in compliance with any agreement in effect between the MSO and a content provider. In no event shall ATX Networks Corp. or any of its affiliates be liable to an MSO, any end user of the UCrypt product, or any other third party, for any claims arising out of or related to any use or misuse of the UCrypt product in contravention of this disclaimer. It is the express obligation of an MSO to convey this disclaimer to any other end user of the UCrypt product.

MDU Solutions®, UCrypt®, DigiVu® and VersActive®Pro are registered trademarks of ATX in the United States and/or other countries. Products or features contained herein may be covered by one or more U.S. or foreign patents. Other non-ATX product and company names in this manual are the property of their respective companies.



1-501 Clements Road West, Ajax, ON L1S 7H4 Canada
Tel +1 (905) 428-6068 Toll Free +1 (800) 565-7488
Fax +1 (905) 427-1964 Toll Free Fax +1 (866) 427-1964
www.atxnetworks.com support@atxnetworks.com