



**DSU-2P**  
(front view)

# DSU-2P

## 1 GHz 80 dB EMI MATV Power Passing Splitter

### Features

- Broadband 5 to 1000 MHz frequency range
- High performance printed board circuitry provides improved hum modulation and intermodulation parameters to ensure superior signal quality
- Yellow-chromate plated zinc-alloy diecast housing ensures excellent ground bonding and long corrosion-free service life in indoor/outdoor applications
- Epoxy-sealed back cover provides effective EMI-RFI shielding > -80 dB, eliminating signal ingress to provide distortion-free pictures
- 1-inch centered 3/8" long precision machined F connector threads ensure improved port-to-connector interface and accommodate external security devices
- High retention seizing pins provide improved connectivity to connector center lead

### Specifications

#### DSU-2P

MHz	INSERTION LOSS (Max. dB)	ISOLATION (Min. dB)	INPUT/OUTPUT RETURN LOSS (Min. dB)	RFI
5-400	3.6	20	18	> 80 dB
400-500	3.8	24	18	> 80 dB
470-600	4.0	23	18	> 80 dB
600-1000	4.0	20	18	> 80 dB

### Ordering Information

Part Number	Description
<b>DSU-2P</b>	2-port 1 GHz Power Passing Splitter
<b>DSU-3P</b>	3-port 1 GHz Power Passing Splitter
<b>DSU-4P</b>	4-port 1 GHz Power Passing Splitter
<b>DSU-8P</b>	8-port 1 GHz Power Passing Splitter
<b>MS-2D</b>	2-port 1 GHz Power Passing Splitter

Products or features contained herein may be covered by one or more U.S. or foreign patents. Other non-ATX product and company names mentioned in this data sheet are the property of their respective companies.

© 2018 ATX Networks  
Printed in Canada  
Information in this document is subject to change without notice.  
Rev. 09/18 (ANW1319)



**ATX Networks**

1-501 Clements Road West, Ajax, ON L1S 7H4 Canada  
Tel: 905.428.6068 | Toll Free: 800.565.7488 | support@atxnetworks.com